

KINEMATIC BEAM BENDERS

BBK-19 SERIES




BBK-19-030-NN Shown.



Low Power Laser Series

4X M4 THD.




← 1000

1"-32 THD. "C" MOUNT

1.125





1.563

2.000

28 - 28mm (1.1")

040 - 4.0mm

064 - 6.4mm

W - Water

FOR MOUNTING

Mirror Correction

90° Beam Displacement

Easy Optic Removal/Replacement

Independent Angular Orthogonal

The BBK-19 series kinematic laser beam benders provide a ninety-degree beam displacement with a 19mm clear aperture.

Independent angular orthogonal mirror correction with eighty pitch adjustment screws provides precise, repeatable alignment. Optic removal and replacement can be accomplished without affecting alignment. Several mirror diameters and thicknesses can be accommodated. Both mounting faces have 1"-32 female threads.

BBK-19 Specifications

- ±2° Independent Orthogonal Mirror Adjustment
- 80 Pitch Adjustment Screws
- Accommodates 25mm & 28mm Diameter Mirrors (other diameters available)
- 1"-32 Mounting Thread (C-Mount)
- Face and Side Mounting Holes
- Available for All Wavelengths
- Sealed Design
- Anodized Aluminum Construction
- 19mm Clear Aperture

N - None N - None I - Interlock

Specifications subject to change without notice. Consult Haas Laser Technologies for Details

